


**1/8" SEALED BRASS CE SAFETY VALVE**

PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-282	1/8"	0,1 BAR	10 unit
YKS-283	1/8"	0,2 BAR	10 unit
YKS-284	1/8"	0,3 BAR	10 unit
YKS-285	1/8"	0,4 BAR	10 unit
YKS-286	1/8"	0,5 BAR	10 unit
YKS-287	1/8"	0,6 BAR	10 unit
YKS-288	1/8"	0,7 BAR	10 unit
YKS-289	1/8"	0,8 BAR	10 unit
YKS-290	1/8"	0,9 BAR	10 unit
YKS-291	1/8"	1,0 BAR	10 unit
YKS-292	1/8"	1,1 BAR	10 unit
YKS-293	1/8"	1,2 BAR	10 unit
YKS-294	1/8"	1,3 BAR	10 unit
YKS-295	1/8"	1,4 BAR	10 unit
YKS-296	1/8"	1,5 BAR	10 unit
YKS-297	1/8"	1,6 BAR	10 unit
YKS-298	1/8"	1,7 BAR	10 unit
YKS-299	1/8"	1,8 BAR	10 unit
YKS-300	1/8"	1,9 BAR	10 unit



- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

**1/8" BRASS SAFETY VALVE TECHNICAL SPECIFICATIONS**

<b>BODY MATERIAL</b>	BRASS (MS58)
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NİTRİLE
<b>ORIFACE DIAMETER</b>	6,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	17 mm ( 15 HEXOGEN)
<b>LENGHT</b>	45 mm
<b>WEIGHT</b>	40 gr

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS


## 1/8" SEALED STAINLESS CE SAFETY VALVE



PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-3001	1/8"	0,1 BAR	10 unit
YKS-3002	1/8"	0,2 BAR	10 unit
YKS-3003	1/8"	0,3 BAR	10 unit
YKS-3004	1/8"	0,4 BAR	10 unit
YKS-3005	1/8"	0,5 BAR	10 unit
YKS-3006	1/8"	0,6 BAR	10 unit
YKS-3007	1/8"	0,7 BAR	10 unit
YKS-3008	1/8"	0,8 BAR	10 unit
YKS-3009	1/8"	0,9 BAR	10 unit
YKS-3010	1/8"	1,0 BAR	10 unit
YKS-3011	1/8"	1,1 BAR	10 unit
YKS-3012	1/8"	1,2 BAR	10 unit
YKS-3013	1/8"	1,3 BAR	10 unit
YKS-3014	1/8"	1,4 BAR	10 unit
YKS-3015	1/8"	1,5 BAR	10 unit
YKS-3016	1/8"	1,6 BAR	10 unit
YKS-3017	1/8"	1,7 BAR	10 unit
YKS-3018	1/8"	1,8 BAR	10 unit
YKS-3019	1/8"	1,9 BAR	10 unit

### 1/8" STAINLESS SAFETY VALVE TECHNICAL SPECIFICATIONS

<b>BODY MATERIAL</b>	STAINLESS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NITRILE
<b>ORIFACE DIAMETER</b>	6,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	17 mm ( 15 HEXOGEN)
<b>LENGHT</b>	45 mm
<b>WEIGHT</b>	40 gr




- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS

**1/8" SEALED CHROME PLATED BRASS CE SAFETY VALVE**

PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-6001	1/8"	0,1 BAR	10 ADET
YKS-6002	1/8"	0,2 BAR	10 ADET
YKS-6003	1/8"	0,3 BAR	10 ADET
YKS-6004	1/8"	0,4 BAR	10 ADET
YKS-6005	1/8"	0,5 BAR	10 ADET
YKS-6006	1/8"	0,6 BAR	10 ADET
YKS-6007	1/8"	0,7 BAR	10 ADET
YKS-6008	1/8"	0,8 BAR	10 ADET
YKS-6009	1/8"	0,9 BAR	10 ADET
YKS-6010	1/8"	1,0 BAR	10 ADET
YKS-6011	1/8"	1,1 BAR	10 ADET
YKS-6012	1/8"	1,2 BAR	10 ADET
YKS-6013	1/8"	1,3 BAR	10 ADET
YKS-6014	1/8"	1,4 BAR	10 ADET
YKS-6015	1/8"	1,5 BAR	10 ADET
YKS-6016	1/8"	1,6 BAR	10 ADET
YKS-6017	1/8"	1,7 BAR	10 ADET
YKS-6018	1/8"	1,8 BAR	10 ADET
YKS-6019	1/8"	1,9 BAR	10 ADET



- 1 – VALVE BODY
- 2 – BALANCE SHAFT
- 3 – ADJUSTING NUT
- 4 – GASKET
- 5 – GASKET BEARING
- 6 – PRESSURE BEARING

**1/8" CHROME PLATED SAFETY VALVE TECHNICAL SPECIFICATIONS**

<b>BODY MATERIAL</b>	CHROME PLATED BRASS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NİTRİLE
<b>ORIFACE DIAMETER</b>	6,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESIGN PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORROSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	17 mm ( 15 HEXOGEN )
<b>LENGTH</b>	45 mm
<b>WEIGHT</b>	40 gr

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS


## 1/4" SEALED BRASS CE SAFETY VALVE



PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-301	1/8"	0,1 BAR	10 ADET
YKS-302	1/8"	0,2 BAR	10 ADET
YKS-303	1/8"	0,3 BAR	10 ADET
YKS-304	1/8"	0,4 BAR	10 ADET
YKS-305	1/8"	0,5 BAR	10 ADET
YKS-306	1/8"	0,6 BAR	10 ADET
YKS-307	1/8"	0,7 BAR	10 ADET
YKS-308	1/8"	0,8 BAR	10 ADET
YKS-309	1/8"	0,9 BAR	10 ADET
YKS-310	1/8"	1,0 BAR	10 ADET
YKS-311	1/8"	1,1 BAR	10 ADET
YKS-312	1/8"	1,2 BAR	10 ADET
YKS-313	1/8"	1,3 BAR	10 ADET
YKS-314	1/8"	1,4 BAR	10 ADET
YKS-315	1/8"	1,5 BAR	10 ADET
YKS-316	1/8"	1,6 BAR	10 ADET
YKS-317	1/8"	1,7 BAR	10 ADET
YKS-318	1/8"	1,8 BAR	10 ADET
YKS-319	1/8"	1,9 BAR	10 ADET

### 1/4" BRASS SAFETY VALVE TECHNICAL SPECIFICATIONS

<b>BODY MATERIAL</b>	BRASS (MS58)
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NITRILE
<b>ORIFACE DIAMETER</b>	6,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	17 mm ( 15 HEXOGEN )
<b>LENGHT</b>	45 mm
<b>WEIGHT</b>	40 gr




- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS

**1/4" SEALED STAINLESS CE SAFETY VALVE**

PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-3101	1/4"	0,1 BAR	10 unit
YKS-3102	1/4"	0,2 BAR	10 unit
YKS-3103	1/4"	0,3 BAR	10 unit
YKS-3104	1/4"	0,4 BAR	10 unit
YKS-3105	1/4"	0,5 BAR	10 unit
YKS-3106	1/4"	0,6 BAR	10 unit
YKS-3107	1/4"	0,7 BAR	10 unit
YKS-3108	1/4"	0,8 BAR	10 unit
YKS-3109	1/4"	0,9 BAR	10 unit
YKS-3110	1/4"	1,0 BAR	10 unit
YKS-3111	1/4"	1,1 BAR	10 unit
YKS-3112	1/4"	1,2 BAR	10 unit
YKS-3113	1/4"	1,3 BAR	10 unit
YKS-3114	1/4"	1,4 BAR	10 unit
YKS-3115	1/4"	1,5 BAR	10 unit
YKS-3116	1/4"	1,6 BAR	10 unit
YKS-3117	1/4"	1,7 BAR	10 unit
YKS-3118	1/4"	1,8 BAR	10 unit
YKS-3119	1/4"	1,9 BAR	10 unit



- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

**1/4" STAINLESS SAFETY VALVE TECHNICAL SPECIFICATIONS**

<b>BODY MATERIAL</b>	STAINLESS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NİTRİLE
<b>ORIFACE DIAMETER</b>	6,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	17 mm ( 15 HEXOGEN)
<b>LENGHT</b>	45 mm
<b>WEIGHT</b>	40 gr

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS


## 1/4" SEALED CHROME PLATED BRASS CE SAFETY VALVE



PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-6101	1/8"	0,1 BAR	10 unit
YKS-6102	1/8"	0,2 BAR	10 unit
YKS-6103	1/8"	0,3 BAR	10 unit
YKS-6104	1/8"	0,4 BAR	10 unit
YKS-6105	1/8"	0,5 BAR	10 unit
YKS-6106	1/8"	0,6 BAR	10 unit
YKS-6107	1/8"	0,7 BAR	10 unit
YKS-6108	1/8"	0,8 BAR	10 unit
YKS-6109	1/8"	0,9 BAR	10 unit
YKS-6110	1/8"	1,0 BAR	10 unit
YKS-6111	1/8"	1,1 BAR	10 unit
YKS-6112	1/8"	1,2 BAR	10 unit
YKS-6113	1/8"	1,3 BAR	10 unit
YKS-6114	1/8"	1,4 BAR	10 unit
YKS-6115	1/8"	1,5 BAR	10 unit
YKS-6116	1/8"	1,6 BAR	10 unit
YKS-6117	1/8"	1,7 BAR	10 unit
YKS-6118	1/8"	1,8 BAR	10 unit
YKS-6119	1/8"	1,9 BAR	10 unit

### 1/4" CHORME PLATED SAFETY VALVE TECHNICAL SPECIFICATIONS

<b>BODY MATERIAL</b>	CHROME PLATED BRASS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NITRILE
<b>ORIFACE DIAMETER</b>	6,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	17 mm ( 15 HEXOGEN)
<b>LENGHT</b>	45 mm
<b>WEIGHT</b>	40 gr




- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS

**3/8" SEALED BRASS CE SAFETY VALVE**

PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-320	3/8"	0,1 BAR	10 unit
YKS-321	3/8"	0,2 BAR	10 unit
YKS-322	3/8"	0,3 BAR	10 unit
YKS-323	3/8"	0,4 BAR	10 unit
YKS-324	3/8"	0,5 BAR	10 unit
YKS-325	3/8"	0,6 BAR	10 unit
YKS-326	3/8"	0,7 BAR	10 unit
YKS-327	3/8"	0,8 BAR	10 unit
YKS-328	3/8"	0,9 BAR	10 unit
YKS-329	3/8"	1,0 BAR	10 unit
YKS-330	3/8"	1,1 BAR	10 unit
YKS-331	3/8"	1,2 BAR	10 unit
YKS-332	3/8"	1,3 BAR	10 unit
YKS-333	3/8"	1,4 BAR	10 unit
YKS-334	3/8"	1,5 BAR	10 unit
YKS-335	3/8"	1,6 BAR	10 unit
YKS-336	3/8"	1,7 BAR	10 unit
YKS-337	3/8"	1,8 BAR	10 unit
YKS-338	3/8"	1,9 BAR	10 unit



- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

3/8" BRASS SAFETY VALVE TECHNICAL SPECIFICATIONS	
<b>BODY MATERIAL</b>	BRASS (MS58)
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NİTRİLE
<b>ORIFACE DIAMETER</b>	10,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	26 mm ( 22 HEXOGEN)
<b>LENGHT</b>	57 mm
<b>WEIGHT</b>	95 gr

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS


### 3/8" SEALED STAINLESS CE SAFETY VALVE



PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-3201	3/8"	0,1 BAR	10 unit
YKS-3202	3/8"	0,2 BAR	10 unit
YKS-3203	3/8"	0,3 BAR	10 unit
YKS-3204	3/8"	0,4 BAR	10 unit
YKS-3205	3/8"	0,5 BAR	10 unit
YKS-3206	3/8"	0,6 BAR	10 unit
YKS-3207	3/8"	0,7 BAR	10 unit
YKS-3208	3/8"	0,8 BAR	10 unit
YKS-3209	3/8"	0,9 BAR	10 unit
YKS-3210	3/8"	1,0 BAR	10 unit
YKS-3211	3/8"	1,1 BAR	10 unit
YKS-3212	3/8"	1,2 BAR	10 unit
YKS-3213	3/8"	1,3 BAR	10 unit
YKS-3214	3/8"	1,4 BAR	10 unit
YKS-3215	3/8"	1,5 BAR	10 unit
YKS-3216	3/8"	1,6 BAR	10 unit
YKS-3217	3/8"	1,7 BAR	10 unit
YKS-3218	3/8"	1,8 BAR	10 unit
YKS-3219	3/8"	1,9 BAR	10 unit

#### 3/8" STAINLESS SAFETY VALVE TECHNICAL SPECIFICATIONS

<b>BODY MATERIAL</b>	STAINLESS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NITRILE
<b>ORIFACE DIAMETER</b>	10,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	26 mm ( 22 HEXOGEN)
<b>LENGHT</b>	57 mm
<b>WEIGHT</b>	95 gr




- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS

**3/8" SEALED CHROME PLATED BRASS CE SAFETY VALVE**

PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-6201	3/8"	0,1 BAR	10 unit
YKS-6202	3/8"	0,2 BAR	10 unit
YKS-6203	3/8"	0,3 BAR	10 unit
YKS-6204	3/8"	0,4 BAR	10 unit
YKS-6205	3/8"	0,5 BAR	10 unit
YKS-6206	3/8"	0,6 BAR	10 unit
YKS-6207	3/8"	0,7 BAR	10 unit
YKS-6208	3/8"	0,8 BAR	10 unit
YKS-6209	3/8"	0,9 BAR	10 unit
YKS-6210	3/8"	1,0 BAR	10 unit
YKS-6211	3/8"	1,1 BAR	10 unit
YKS-6212	3/8"	1,2 BAR	10 unit
YKS-6213	3/8"	1,3 BAR	10 unit
YKS-6214	3/8"	1,4 BAR	10 unit
YKS-6215	3/8"	1,5 BAR	10 unit
YKS-6216	3/8"	1,6 BAR	10 unit
YKS-6217	3/8"	1,7 BAR	10 unit
YKS-6218	3/8"	1,8 BAR	10 unit
YKS-6219	3/8"	1,9 BAR	10 unit



- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

**3/8" CHROME PLATED SAFETY VALVE TECHNICAL SPECIFICATIONS**

<b>BODY MATERIAL</b>	CHROME PLATED BRASS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NİTRİLE
<b>ORIFACE DIAMETER</b>	10,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	26 mm ( 22 HEXOGEN)
<b>LENGHT</b>	57 mm
<b>WEIGHT</b>	95 gr

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS


## 1/2" SEALED BRASS CE SAFETY VALVE



PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-339	1/2"	0,1 BAR	10 unit
YKS-340	1/2"	0,2 BAR	10 unit
YKS-341	1/2"	0,3 BAR	10 unit
YKS-342	1/2"	0,4 BAR	10 unit
YKS-343	1/2"	0,5 BAR	10 unit
YKS-344	1/2"	0,6 BAR	10 unit
YKS-345	1/2"	0,7 BAR	10 unit
YKS-346	1/2"	0,8 BAR	10 unit
YKS-347	1/2"	0,9 BAR	10 unit
YKS-348	1/2"	1,0 BAR	10 unit
YKS-349	1/2"	1,1 BAR	10 unit
YKS-350	1/2"	1,2 BAR	10 unit
YKS-351	1/2"	1,3 BAR	10 unit
YKS-352	1/2"	1,4 BAR	10 unit
YKS-353	1/2"	1,5 BAR	10 unit
YKS-354	1/2"	1,6 BAR	10 unit
YKS-355	1/2"	1,7 BAR	10 unit
YKS-356	1/2"	1,8 BAR	10 unit
YKS-357	1/2"	1,9 BAR	10 unit

### 1/2" BRASS SAFETY VALVE TECHNICAL SPECIFICATIONS

<b>BODY MATERIAL</b>	BRASS (MS58)
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NITRILE
<b>ORIFACE DIAMETER</b>	10,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	26 mm ( 22 HEXOGEN)
<b>LENGHT</b>	57 mm
<b>WEIGHT</b>	100 gr




- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS

**1/2" SEALED STAINLESS CE SAFETY VALVE**

PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-3301	1/2"	0,1 BAR	10 unit
YKS-3302	1/2"	0,2 BAR	10 unit
YKS-3303	1/2"	0,3 BAR	10 unit
YKS-3304	1/2"	0,4 BAR	10 unit
YKS-3305	1/2"	0,5 BAR	10 unit
YKS-3306	1/2"	0,6 BAR	10 unit
YKS-3307	1/2"	0,7 BAR	10 unit
YKS-3308	1/2"	0,8 BAR	10 unit
YKS-3309	1/2"	0,9 BAR	10 unit
YKS-3310	1/2"	1,0 BAR	10 unit
YKS-3311	1/2"	1,1 BAR	10 unit
YKS-3312	1/2"	1,2 BAR	10 unit
YKS-3313	1/2"	1,3 BAR	10 unit
YKS-3314	1/2"	1,4 BAR	10 unit
YKS-3315	1/2"	1,5 BAR	10 unit
YKS-3316	1/2"	1,6 BAR	10 unit
YKS-3317	1/2"	1,7 BAR	10 unit
YKS-3318	1/2"	1,8 BAR	10 unit
YKS-3319	1/2"	1,9 BAR	10 unit



- 1 – VALVE BODY
- 2 – BALANCE SHAFT
- 3 – ADJUSTING NUT
- 4 – GASKET
- 5 – GASKET BEARING
- 6 – PRESSURE BEARING

**1/2" STAINLESS SAFETY VALVE TECHNICAL SPECIFICATIONS**

<b>BODY MATERIAL</b>	STAINLESS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NİTRİLE
<b>ORIFACE DIAMETER</b>	10,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	26 mm ( 22 HEXOGEN)
<b>LENGHT</b>	57 mm
<b>WEIGHT</b>	100 gr

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS


## 1/2" SEALED CHROME PLATED BRASS CE SAFETY VALVE



PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-6301	1/2"	0,1 BAR	10 unit
YKS-6302	1/2"	0,2 BAR	10 unit
YKS-6303	1/2"	0,3 BAR	10 unit
YKS-6304	1/2"	0,4 BAR	10 unit
YKS-6305	1/2"	0,5 BAR	10 unit
YKS-6306	1/2"	0,6 BAR	10 unit
YKS-6307	1/2"	0,7 BAR	10 unit
YKS-6308	1/2"	0,8 BAR	10 unit
YKS-6309	1/2"	0,9 BAR	10 unit
YKS-6310	1/2"	1,0 BAR	10 unit
YKS-6311	1/2"	1,1 BAR	10 unit
YKS-6312	1/2"	1,2 BAR	10 unit
YKS-6313	1/2"	1,3 BAR	10 unit
YKS-6314	1/2"	1,4 BAR	10 unit
YKS-6315	1/2"	1,5 BAR	10 unit
YKS-6316	1/2"	1,6 BAR	10 unit
YKS-6317	1/2"	1,7 BAR	10 unit
YKS-6318	1/2"	1,8 BAR	10 unit
YKS-6319	1/2"	1,9 BAR	10 unit

### 1/2" CHROME PLATED SAFETY VALVE TECHNICAL SPECIFICATIONS

<b>BODY MATERIAL</b>	CHROME PLATED BRASS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NITRILE
<b>ORIFACE DIAMETER</b>	10,8 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	26 mm ( 22 HEXOGEN)
<b>LENGHT</b>	57 mm
<b>WEIGHT</b>	100 gr




- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS

**3/4" SEALED BRASS CE SAFETY VALVE**

PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-358	3/4"	0,1 BAR	5 unit
YKS-359	3/4"	0,2 BAR	5 unit
YKS-360	3/4"	0,3 BAR	5 unit
YKS-361	3/4"	0,4 BAR	5 unit
YKS-362	3/4"	0,5 BAR	5 unit
YKS-363	3/4"	0,6 BAR	5 unit
YKS-364	3/4"	0,7 BAR	5 unit
YKS-365	3/4"	0,8 BAR	5 unit
YKS-366	3/4"	0,9 BAR	5 unit
YKS-367	3/4"	1,0 BAR	5 unit
YKS-368	3/4"	1,1 BAR	5 unit
YKS-369	3/4"	1,2 BAR	5 unit
YKS-370	3/4"	1,3 BAR	5 unit
YKS-371	3/4"	1,4 BAR	5 unit
YKS-372	3/4"	1,5 BAR	5 unit
YKS-373	3/4"	1,6 BAR	5 unit
YKS-374	3/4"	1,7 BAR	5 unit
YKS-375	3/4"	1,8 BAR	5 unit
YKS-376	3/4"	1,9 BAR	5 unit



- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

3/4" BRASS SAFETY VALVE TECHNICAL SPECIFICATIONS	
<b>BODY MATERIAL</b>	BRASS (MS58)
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NİTRİLİ
<b>ORIFACE DIAMETER</b>	14 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	32 mm ( 28 HEXOGEN )
<b>LENGHT</b>	91 mm
<b>WEIGHT</b>	245 gr

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS


## 3/4" SEALED STAINLESS CE SAFETY VALVE



PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-3401	3/4"	0,1 BAR	5 unit
YKS-3402	3/4"	0,2 BAR	5 unit
YKS-3403	3/4"	0,3 BAR	5 unit
YKS-3404	3/4"	0,4 BAR	5 unit
YKS-3405	3/4"	0,5 BAR	5 unit
YKS-3406	3/4"	0,6 BAR	5 unit
YKS-3407	3/4"	0,7 BAR	5 unit
YKS-3408	3/4"	0,8 BAR	5 unit
YKS-3409	3/4"	0,9 BAR	5 unit
YKS-3410	3/4"	1,0 BAR	5 unit
YKS-3411	3/4"	1,1 BAR	5 unit
YKS-3412	3/4"	1,2 BAR	5 unit
YKS-3413	3/4"	1,3 BAR	5 unit
YKS-3414	3/4"	1,4 BAR	5 unit
YKS-3415	3/4"	1,5 BAR	5 unit
YKS-3416	3/4"	1,6 BAR	5 unit
YKS-3417	3/4"	1,7 BAR	5 unit
YKS-3418	3/4"	1,8 BAR	5 unit
YKS-3419	3/4"	1,9 BAR	5 unit

### 3/4" STAINLESS SAFETY VALVE TECHNICAL SPECIFICATIONS

<b>BODY MATERIAL</b>	STAINLESS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NITRILE
<b>ORIFACE DIAMETER</b>	14 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	32 mm ( 28 HEXOGEN)
<b>LENGHT</b>	91 mm
<b>WEIGHT</b>	245 gr




- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS

**3/4" SEALED CHROME PLATED BRASS CE SAFETY VALVE**

PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-6401	3/4"	0,1 BAR	5 unit
YKS-6402	3/4"	0,2 BAR	5 unit
YKS-6403	3/4"	0,3 BAR	5 unit
YKS-6404	3/4"	0,4 BAR	5 unit
YKS-6405	3/4"	0,5 BAR	5 unit
YKS-6406	3/4"	0,6 BAR	5 unit
YKS-6407	3/4"	0,7 BAR	5 unit
YKS-6408	3/4"	0,8 BAR	5 unit
YKS-6409	3/4"	0,9 BAR	5 unit
YKS-6410	3/4"	1,0 BAR	5 unit
YKS-6411	3/4"	1,1 BAR	5 unit
YKS-6412	3/4"	1,2 BAR	5 unit
YKS-6413	3/4"	1,3 BAR	5 unit
YKS-6414	3/4"	1,4 BAR	5 unit
YKS-6415	3/4"	1,5 BAR	5 unit
YKS-6416	3/4"	1,6 BAR	5 unit
YKS-6417	3/4"	1,7 BAR	5 unit
YKS-6418	3/4"	1,8 BAR	5 unit
YKS-6419	3/4"	1,9 BAR	5 unit



- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

**3/4" CHROME PLATED SAFETY VALVE TECHNICAL SPECIFICATIONS**

<b>BODY MATERIAL</b>	CHROME PLATED BRASS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NİTRİLE
<b>ORIFACE DIAMETER</b>	14 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	32 mm ( 28 HEXOGEN)
<b>LENGHT</b>	91 mm
<b>WEIGHT</b>	245 gr

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS


## 1" SEALED BRASS CE SAFETY VALVE



PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-377	1"	0,1 BAR	1 unit
YKS-378	1"	0,2 BAR	1 unit
YKS-379	1"	0,3 BAR	1 unit
YKS-380	1"	0,4 BAR	1 unit
YKS-381	1"	0,5 BAR	1 unit
YKS-382	1"	0,6 BAR	1 unit
YKS-383	1"	0,7 BAR	1 unit
YKS-384	1"	0,8 BAR	1 unit
YKS-385	1"	0,9 BAR	1 unit
YKS-386	1"	1,0 BAR	1 unit
YKS-387	1"	1,1 BAR	1 unit
YKS-388	1"	1,2 BAR	1 unit
YKS-389	1"	1,3 BAR	1 unit
YKS-390	1"	1,4 BAR	1 unit
YKS-391	1"	1,5 BAR	1 unit
YKS-392	1"	1,6 BAR	1 unit
YKS-393	1"	1,7 BAR	1 unit
YKS-394	1"	1,8 BAR	1 unit
YKS-395	1"	1,9 BAR	1 unit

### 1" BRASS SAFETY VALVE TECHNICAL SPECIFICATIONS

<b>BODY MATERIAL</b>	BRASS (MS58)
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NITRILE
<b>ORIFACE DIAMETER</b>	20,5 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	42 mm ( 36 HEXOGEN)
<b>LENGHT</b>	118 mm
<b>WEIGHT</b>	495 gr




- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS

**1" SEALED STAINLESS CE SAFETY VALVE**

PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-3501	1"	0,1 BAR	1 unit
YKS-3502	1"	0,2 BAR	1 unit
YKS-3503	1"	0,3 BAR	1 unit
YKS-3504	1"	0,4 BAR	1 unit
YKS-3505	1"	0,5 BAR	1 unit
YKS-3506	1"	0,6 BAR	1 unit
YKS-3507	1"	0,7 BAR	1 unit
YKS-3508	1"	0,8 BAR	1 unit
YKS-3509	1"	0,9 BAR	1 unit
YKS-3510	1"	1,0 BAR	1 unit
YKS-3511	1"	1,1 BAR	1 unit
YKS-3512	1"	1,2 BAR	1 unit
YKS-3513	1"	1,3 BAR	1 unit
YKS-3514	1"	1,4 BAR	1 unit
YKS-3515	1"	1,5 BAR	1 unit
YKS-3516	1"	1,6 BAR	1 unit
YKS-3517	1"	1,7 BAR	1 unit
YKS-3518	1"	1,8 BAR	1 unit
YKS-3519	1"	1,9 BAR	1 unit



- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

1" STAINLESS SAFETY VALVE TECHNICAL SPECIFICATIONS	
<b>BODY MATERIAL</b>	STAINLESS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NİTRİLE
<b>ORIFACE DIAMETER</b>	20,5 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	42 mm ( 36 HEXOGEN )
<b>LENGHT</b>	118 mm
<b>WEIGHT</b>	495 gr

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS


## 1" SEALED CHROME PLATED BRASS CE SAFETY VALVE



PRODUCT CODE	CONNECTION SIZE	DISCHARGE STARTING PRESSURE	PACKAGE QUANTITY
YKS-6501	1"	0,1 BAR	1 unit
YKS-6502	1"	0,2 BAR	1 unit
YKS-6503	1"	0,3 BAR	1 unit
YKS-6504	1"	0,4 BAR	1 unit
YKS-6505	1"	0,5 BAR	1 unit
YKS-6506	1"	0,6 BAR	1 unit
YKS-6507	1"	0,7 BAR	1 unit
YKS-6508	1"	0,8 BAR	1 unit
YKS-6509	1"	0,9 BAR	1 unit
YKS-6510	1"	1,0 BAR	1 unit
YKS-6511	1"	1,1 BAR	1 unit
YKS-6512	1"	1,2 BAR	1 unit
YKS-6513	1"	1,3 BAR	1 unit
YKS-6514	1"	1,4 BAR	1 unit
YKS-6515	1"	1,5 BAR	1 unit
YKS-6516	1"	1,6 BAR	1 unit
YKS-6517	1"	1,7 BAR	1 unit
YKS-6518	1"	1,8 BAR	1 unit
YKS-6519	1"	1,9 BAR	1 unit

### 1" CHROME PLATED SAFETY VALVE TECHNICAL SPECIFICATIONS

<b>BODY MATERIAL</b>	CHROME PLATED BRASS
<b>SPRING QUALITY</b>	STAINLESS
<b>SEALING</b>	SILICON
<b>SEALING OPTIONAL</b>	VITON - TEFLON - NITRILE
<b>ORIFACE DIAMETER</b>	20,5 mm
<b>OPERATING TEMPERATURE</b>	(- 50 / + 250)
<b>MAX.OPENING VALUE</b>	( + %7 )
<b>SHUTDOWN PRESSURE VALUE</b>	( - %20 )
<b>BODY DESİNG PRESSURE</b>	50 BAR (725 PSI)
<b>STANDARD</b>	TS EN 13445-3
<b>DIRECTIVE</b>	2014 / 68 EU
<b>GENERAL AREAS OF USE</b>	AIR , WATER , STEAM , OIL
<b>SPECIAL LIQUID USE AREAS</b>	NON-CORRSIVE LIQUIDS
<b>SPECIAL GAS USES</b>	NON-HAZARDOUS GASES
<b>OUTER DIAMETER</b>	42 mm ( 36 HEXOGEN)
<b>LENGHT</b>	118 mm
<b>WEIGHT</b>	495 gr



- 1 - VALVE BODY
- 2 - BALANCE SHAFT
- 3 - ADJUSTING NUT
- 4 - GASKET
- 5 - GASKET BEARING
- 6 - PRESSURE BEARING

OUR PRODUCTS ARE DELIVERED WITH A CERTIFICATE WITH TECHNICAL SPECIFICATIONS AND SERIAL NUMBER. OUR PRODUCTS HAVE CE CERTIFICATE IN ACCORDANCE WITH 2014 / 68 EU PRESSURE EQUIPMENT REGULATION, PLEASE SPECIFY THE USAGE AREA IN YOUR PRODUCT ORDERS